

**///Rowmark®**

PaintPlus™



primary paints

/// Make Your Mark

rowmark.com / 877.ROWMARK

## Primary PaintPlus kit includes: 12 of the following colors in 2 FL OZ or 8FL OZ jars:

<i>Color</i>	<i>Name</i>	<i>2 FL OZ (59,15 mL)</i>	<i>8FL OZ (236,6 mL)</i>
	Red	RP601-2	RP601-8
	Yellow	RP701-2	RP701-8
	Orange	RP651-2	RP651-8
	Light Blue	RP562-2	RP562-8
	Blue	RP501-2	RP501-8
	Purple	RP582-2	RP582-8
	Ocean Blue	RP592-2	RP592-8
	Pine Green	RP902-2	RP902-8
	Bright White	RP204-2	RP204-8
	Black	RP401-2	RP401-8
	Silver	RP304-2	RP304-8
	Gold	RP771-2	RP771-8

### 2 FL OZ (59,15 mL) kit:

Item Code: RPKIT-2

Kit contains: twelve, 2 FL OZ jars of PaintPlus Primary Paint colors and two, one inch foam applicators.

### 8 FL OZ (236,6 mL) kit:

Item Code: RPKIT-8

Kit contains: twelve, 8 FL OZ jars of PaintPlus Primary Paint colors and two, one inch and two, three inch foam applicators.

All Primary PaintPlus paints are also available individually.

*Please carefully read these instructions and warnings before using this product.*

## Where to Use

Properly prepared acrylic surface.

## Drying Time

Dry to the touch in 30-45 minutes. Paint only when air temperatures are 50-90°F (10-32°C).

## Surface Preparation

Thoroughly clean the surface and allow to dry.

## **Application/Clean-Up**

Stir/Shake paint thoroughly to ensure uniform color. Finish with long, even strokes in one direction. Clean brush and hands with warm, soapy water.

## **Usage**

Color filling requires a little bit of technique and preparation for optimal results. We recommend the following steps to prep the piece before painting or color filling. First, mask the edges of the plate to avoid over-painting. Use a soft cloth, paper towel, or other non-abrasive material underneath your plate.

## **For Best Results**

Generally two coats of PaintPlus paints are required to get the best coverage and block any small holes that form in the paint from air pockets. Make one application from top to bottom and the second coat from bottom to top to get coverage on all of the character edges.

Rowmark does recommend that you completely cover the back of the finished sign or badge with paint to avoid any shadows when viewed from the front. This is not necessary if the substrate will be mounted on another surface or a backer plate is used.

For exterior applications, Rowmark recommends adhering a backer plate to the painted surface to minimize exposure to moisture.

## **Storage & Disposal**

Do not freeze. Keep container closed when not in use. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

## **Additional Resources & Support**

For more information about painting Rowmark materials visit the Technical Help section on [rowmark.com](http://rowmark.com).

MSDS information for PaintPlus products are available on [rowmark.com](http://rowmark.com)

